



Cosmic 32M
Electric Wire Stripper



Cosmic 927R
Micro-Cable Stripper



Kappa 330
Automatic Stripping Machine



Cosmic 60R
Semi-Automatic Stripper



K206
Cutting Machine

Wire Preparation Equipment

Cosmic 32M Electric Wire Stripper

- Digital display of stripping diameter
- Full or partial strip
- Wire range: 12 - 32 AWG
- High speed cycle time @ 0.3 seconds

The Cosmic 32M is the latest high-speed electric wire stripper. Achieving higher precision, more power, and a wider AWG range, all in quicker cycle time than its predecessor. Equipped with a digital stripping diameter display and a sensitive wire-tip touchsensor for easy operation.

Sold and distributed only in North America.

Cosmic 60R Rotary-Jacket Stripper

- Strip different wire sizes without changing the blades
- Easy to adjust cutting diameter by micrometer dial knob
- Digital Display for stripping diameter
- Full or partial strip

The Cosmic 60R is designed for jacket stripping of multi-conductor or single cable. Its patented rotary blade centralizer system can strip various insulation material cables without changing the blades. It comes equipped with a digital display for setting the wire and cable diameters.

Sold and distributed only in North America.

Cosmic 927R and Cosmic 927RX Micro-Cable Strippers

- Digital display of wire diameter
- Can be selected to twist with clockwise/counterclockwise or non-twist
- Wire range: 10-36 AWG
- Cycle time 1.5 seconds maximum

The demand for a precision cable stripper that can handle various wire insulation materials such as small and compact electronic devices and communication equipment has been met. The Cosmic 927R was designed and developed to reliably strip various insulation materials and micro-cable. The stripping diameter display can be set to within 0.1mm increments. Thus optimal stripping quality is guaranteed and damage to the conductor is eliminated. **The Cosmic 927RX model shares the features of Cosmic 927R but is recommended for hard to strip insulations.**

Both models sold and distributed only in North America.

K206 Cutting Machine

- Flat Cables
- Round Cables
- Tubes
- PVC Strips
- Foils
- Reproducible setting of roller pressure and cutting force
- Short conversion times without need for tools

Wire Preparation Equipment

	Cosmic 32M	Cosmic 60R	Cosmic 927R (927RX)
Part Number:	5-528367-3	1-528367-3	5-528367-1 (5-528367-4 927RX)
Cross Section Range:	0.3mm ² - 3.0mm ² 32 - 12 AWG	2.5mm ² -16mm ² 14 - 5 AWG	0.01mm ² -5.0mm ² 36 - 10 AWG
Stripping Length:	1.5mm-25mm	20 - 90mm	1.0 - 25mm (1.5-25mm 927RX)
Pull-Off Length:	25mm max.	25mm max.	
Partial Strip:	Yes	Yes	Yes
Insulation Types:	PVC, Teflon, Rubber, etc.	Teflon, Rubber, etc	Teflon, Rubber, PVC, etc
Cycle Time:	0.3 sec.	5 sec.	1.5 sec max.
Electrical:	100-240 VAC	100 - 240 VAC	100-240 VAC
Weight:	4.5kg	20kg	8kg
Dimensions: (L x W x H)	350 x 77 x 175mm	628 x 241 x 230mm	400 x 131 x 218mm

	K206
Part Number:	1-528309-1
Length Range:	1mm - 99999mm
Length Accuracy:	±1mm or ±0.2%, depending on wire length
Wire Cross Sections:	0.14-35mm ² (stranded wire); AWG 26 - 2
Max. Passage Height:	16mm
Max. Passage Width:	82mm

Kappa Family of Automatic Strippers

Kappa family strippers are ideal for cutting individual and special wires to length and stripping them. They can strip in sections, allowing them to strip even extremely long lengths in perfect quality. The machines cover an extraordinarily broad range of cross sections. Kappa 220, 225, and 330 strippers support a variety of processing options such as wire marking with hot-stamp or ink jet markers. Hot stamp marking can even be done on the Kappa 210 stripper, the entry-level model. * Many wires outside the indicated cross section range can be processed on the Kappa strippers. Certain extremely hard, tough wires may not be able to be processed even though they are within the indicated cross section range. In case of doubt, we are happy to produce samples of your wires.

	Kappa 210	Kappa 220	Kappa 225	Kappa 330
Part Number	3-547178-2	3-547178-3	3-547178-0	2-528309-0
Length Range	1mm - 200000mm			
Length Accuracy	±1mm or <0.2% depending on the wire length			
Stripping Lengths				180mm (full) 999.9mm (partial)
Side 1 / Full and Semi Pull-Off	0.5 - 40mm			
Side 1 / Multi-Axis Cutting	bis 999.9mm			
Side 2 / Full Pull-Off	0.5 - 36mm			50mm
Side 2 / Semi Pull-Off or Multi Cutting	0.5 - 999.9mm			999.9mm
Pull-Off Lengths / Side 1	0-99.9mm			
/ Side 2	0-40mm			—
Short Mode	<45mm, can be deactivated			
Wire Cross Sections*	0.05-3mm ² (stranded wire) AWG30-AWG12	0.05-6mm ² (stranded wire) AWG30-AWG10	0.05-10mm ² (stranded wire) AWG30-AWG7	0.22-35mm ² (stranded wire) AWG24-AWG2
Ribbon Cables				
Maximum Width	—	up to 12mm in width	up to 12mm in width	up to 40mm in width
Minimum Width	—	50mm + stripping length		60mm +pull-off lengths
Maximum Outside Diameter	9mm		10.5mm	16mm
Selectable Piece Numbers	1-60000 pieces			
Noise Level	<70dBA			
Electrical Connection	110V ±15%/50-60 Hz 230V ±15% / 50-60Hz automatic changeover			100-120V/47-63 Hz 220-240V 47-63 Hz automatic changeover
Dimensions (W x H x D)	480 x 340 x 390mm		560 x 340 x 390 mm	630 x 365 x 480 mm
Weight	-28kg	-28kg	-36kg	-55kg

Catalog 1654956 / 08-08 / GATD

© 2008 Tyco Electronics Corp. All Rights Reserved. The TE Logo and Tyco Electronics are trademarks. Komax is a registered trademark of Komax AG.

www.tooling.tycoelectronics.com

Tyco Electronics Corporation, Harrisburg, PA 17105. Phone: 717-564-0100; Fax 717-986-3316



Tyco Electronics
Our commitment. Your advantage.